

ISO/IEC 11801 : 2002

ISO/IEC 61156-5

EN 50173-1 : 2002

EN 50288-3-1

ANSI/TIA/EIA 568B.2 : 2002

Brand-Rex Copper Cables - GigaPlus

Communication Cable, U/UTP, 100 Ω, 4x2xAWG 24/1

Electrical Characteristics @ 20°C	Specification	Typical Performance
Conductor Loop Resistance	Max 19 Ω / 100m	16 Ω / 100m
Conductor Resistance Unbalance	Max 2%	0.5%
Dielectric Strength	1.0kV dc or 0.7kV ac for 1 min	100% in process test
Insulation Resistance	>500MΩ.km @ 100-500V test voltage	>5 GΩ.km
Capacitance Unbalance to Earth	Max 160 pF/100m	40 pF/100m
Velocity of Propagation	<534 nsec/100m @ 100MHz	496 nsec/100m @ 100MHz (NVP for hand held testers = 0.69)
Skew	Max 40 nsec/100m @ 100MHz	25 nsec/100m @ 100MHz
Mean Characteristic Impedance	100 Ω +/- 5 Ω @ 100MHz	100 Ω +/- 3 Ω @ 100MHz
Coupling Attenuation up to 1Ghz	Min 40 dB	50dB

Frequency (MHz)	1	4	10	16	20	31.25	62.5	100	155	200	250	
Insertion Loss (dB/100m)	Spec	2.1	4.0	6.3	8.0	9.0	11.4	16.5	21.3	na	na	na
	Typical	1.8	3.6	5.8	7.4	8.3	10.5	15.3	19.8	25.4	29.4	33.4
NEXT (dB)	Spec	65.3	56.3	50.3	47.3	45.8	42.9	38.4	35.3	na	na	na
	Typical	73.3	64.3	58.3	55.2	53.8	50.9	46.4	43.3	40.4	38.8	37.3
PSNEXT (dB)	Spec	62.3	53.3	47.3	44.2	42.8	39.9	35.4	32.3	na	na	na
	Typical	71.3	62.3	56.3	53.2	51.8	48.9	44.4	41.3	38.4	36.8	35.3
ELFEXT (dB / 100m)	Spec	63.8	51.8	43.8	39.7	37.8	33.9	27.9	23.8	na	na	na
	Typical	78.8	66.8	58.8	54.7	52.8	48.9	42.9	38.8	35.0	32.8	31.5
PSELFEXT (dB / 100m)	Spec	60.8	48.8	40.8	36.7	34.8	30.9	24.9	20.8	na	na	na
	Typical	76.8	64.8	56.8	52.7	50.8	46.9	40.9	36.8	33.0	30.8	29.5
Return Loss (dB/100m)	Spec	na	23.1	25.0	25.0	25.0	23.6	21.5	20.1	na	na	na
	Typical	25.0	28.0	30.0	30.0	30.0	38.6	26.5	25.1	23.8	23.0	22.8
ACR (dB / 100m)	Typical	71.5	60.7	52.5	47.8	45.5	40.4	31.1	23.5	15	9.4	3.9
PSACR (dB / 100m)	Typical	69.5	58.7	50.5	45.8	43.5	38.4	29.1	21.5	13	7.4	1.9


Product Part Numbering

Part Number	GPU	GPU-D	GPU-HF1	GPU-HF1-D	GPU-HF3	GPU-HF3-D
Outer Sheath	PVC	PVC	LSZH	LSZH	LSZH	LSZH
Construction	Simplex	Duplex	Simplex	Duplex	Simplex	Duplex
Cable Weight	31.0 kg/km	62.0 kg/km	32.5kg/km	65.0 kg/km	44.0 kg/km	88.0 kg/km
Calorific Value	0.11 k Wh/m	0.22 k Wh/m	0.11 k Wh/m	0.22 k Wh/m	0.18 k Wh/m	0.36 k Wh/m
Outer Diameter (nom)	4.85mm	9.8 x 4.85mm	5.0mm	10.1 x 5.0mm	5.8mm	11.7 x 5.8mm
Sheath Colour	Grey RAL 7037	Grey RAL 7037	Violet RAL 4005	Violet RAL 4005	Blue RAL 5015	Blue RAL 5015
Fire Safety Rating	IEC 60332-1-2	IEC 60332-1-2	IEC 60332-1-2	IEC 60332-1-2	IEC 60332-3-24	IEC 60332-3-24
Acid Gas Emissions	na	na	IEC 60754-1	IEC 60754-1	IEC 60754-1	IEC 60754-1
Smoke Index	na	na	IEC 61034	IEC 61034	IEC 61034	IEC 61034
Packaging	RLX / WRL	WRL	RLX / WRL	WRL	WRL	WRL

Sheath

24 AWG PACW

Polyolefin Insulation



Independent 3rd Party Certification (3P)

PRODUCT DESCRIPTION:

GigaPlus U/UTP 100 Ω 4x2xAWG 24/1 premium grade Class D/Cat5e cable to support Gigabit Ethernet protocol for installation in horizontal and backbone areas.

PRODUCT PERFORMANCE:

Core

Conductor: 24 AWG Plain Annealed Copper Wire

Insulation: Polyolefin

Diameter: 0.94mm Nominal

Pair: 2 of the above cores

Pair Colour: Blue-White, Orange-White, Green-White, Brown-White

Final Assembly

Cable: 4 of the above pairs

Sheath: PVC or LSZH compound

Mechanical and Environmental

Temp - Installation: 0°C to +50°C

Temp - Operation: -20°C to +75°C

Max Tensile Load: 10kg per simplex cable (installation)

Min Bend Radius: 8 x Outer Diameter (installation)
4 x Outer Diameter (operation)

Packaging

RLX 305m Reelex Box
500m Reelex Box

WRL 500m Wooden Reel
1000m Wooden Reel